

Alfa Unterspannbahnen



	1750 Alfa Silver-Roof 230 SK	191 Alfa Rufol UDB-A 230 Strong SK	1746 Alfa Mono-Roof 200/SK	1745 Alfa Mono-Roof 155/SK	180 Alfa Thermo ND SK	165 Alfa Rufol UDB-A Protect 200 SK	186 Alfa Rufol UDB-A 215 PLUS SK	1850 Alfa Rufol UDB-B SK	173 Alfa Rufol UDB-A 165/B/SK	172 Alfa Rufol UDB-A 130/SK	182 Alfa Rufol UDB-C 100/SK
	Neu		Neu	Neu							
											

Eigenschaften	Preis	ab 3,33 €	ab 2,32 €	ab 2,40 €	ab 1,85 €	ab 2,70 €	ab 2,65 €	ab 2,55 €	ab 1,89 €	ab 1,16 €	ab 1,02 €	ab 0,86 €
	Flächengewicht	230 g/m ²	230 g/m ²	200 g/m ²	155 g/m ²	220 g/m ²	200 g/m ²	215 g/m ²	180 g/m ²	170 g/m ²	130 g/m ²	100 g/m ²
	Höchstzugkraft/ Zugfestigkeit längs	450 N/50 mm	740 N/50 mm	340 N/50 mm	290 N/50 mm	360 N/50 mm	380 N/50 mm	335 N/50 mm	260 N/50 mm	350 N/50 mm	300 N/50 mm	230 N/50 mm
	Höchstzugkraft/ Zugfestigkeit quer	430 N/50 mm	700 N/50 mm	245 N/50 mm	225 N/50 mm	260 N/50 mm	240 N/50 mm	395 N/50 mm	250 N/50 mm	230 N/50 mm	280 N/50 mm	220 N/50 mm
	Weiterreißwiderstand/ Nagelschaft längs	230 N	320 N	275 N	170 N	130 N	230 N	200 N	160 N	210 N	130 N	90 N
	Weiterreißwiderstand/ Nagelschaft quer	220 N	350 N	380 N	200 N	160 N	270 N	200 N	170 N	290 N	150 N	100 N
	Dehnung längs	35 %	60 %	50 %	65 %	28 %	45 %	40 %	30 %	70 %	55 %	60 %
	Dehnung quer	40 %	70 %	70 %	90 %	55 %	60 %	50 %	60 %	100 %	35 %	40 %
	sd-Wert (m)	0,14 m	0,02 m	0,02 m	0,07 m	0,13 m	0,14 m	0,09 m	0,13 m	0,02 m	0,02 m	0,02 m
	UV-Beständigkeit	12 Monate	3 Monate	8 Monate	8 Monate	30 Jahre	4 Monate	3 Monate	3 Monate	3 Monate	3 Monate	3 Monate
Freibewitterung	12 Monate	3 Monate	8 Monate	8 Monate	3 Monate	1 Monat	3 Monate	3 Monate	3 Monate	6 Wochen	2 Monate	
Temperaturbeständigkeit	-40 °C bis +100 °C	-40 °C bis +100 °C	-40 °C bis +100 °C	-40 °C bis +100 °C	-40 °C bis +160 °C	-40 °C bis +100 °C	-40 °C bis +90 °C	-40 °C bis +90 °C	-40 °C bis +100 °C	-40 °C bis +100 °C	-40 °C bis +100 °C	
Einsatzgebiete	Unterdeckung	●	●	●	●	●	●	●	●	●	●	●
	Unterspannung	●	●	●	●	●	●	●	●	●	●	○
	Behelfsdeckung	●	●	●	●	●	●	●	●	●	●	○
	Hinterlüftete Steildächer	●	●	●	●	●	●	●	●	●	●	●
	Unbelüftete Steildächer	●	●	●	●	●	●	●	●	●	●	●
	Hinterlüftete Fassaden	●	●	●	●	●	●	○	○	●	●	●

● = Geeignet | ○ = Nicht geeignet